



Areas of Application

Lightweight, handy and water-repellent bags to lock out industrial control panels and bigger plugs.

Details

- Polyester fabric with polyurethane coating: lightweight and robust
- Drawstring to tighten flexible
- To be locked with a padlock
- Fringe-protected seams covered by black bias tape
- Two different sizes available

Material

- Fabric: Polyester 600D
- Coating: Polyurethane

Dimensions

Item	Size	Length:	Width:	Depth:
• P616	small	450 mm	160 mm	160 mm
• P625	large	450 mm	250 mm	250 mm

Temperature Range

- Polypropylene: -20°C to 80°C (-4°F to 176°F)

Chemical Resistance

All approved chemicals listed are based on the manufacturer's specified chemical resistance chart for plastic material only. The results were determined at a room temperature of +20°C/+68°F. All data are subject to environmental variables and product features.

Chemical	Grade
Mineral lubricants	Resistant
Aliphatic hydrocarbons	Resistant
Aromatic hydrocarbons	Conditionally resistant
Gasoline	Conditionally resistant
Weak mineral acids	Resistant
Strong mineral acids	Conditionally resistant
Weak organic acids	Resistant
Strong organic acids	Conditionally resistant
Oxidizing acids	Not resistant
Weak bases	Resistant
Strong bases	Conditionally resistant
Trichloroethylene	Not resistant
Perchloroethylene	Conditionally resistant
Acetone	Conditionally resistant
Alcohols	Resistant
Hot water (hydrolysis resistance)	Conditionally resistant
UV light and weather	Conditionally resistant

Legal Note

ABUS products are sold with the understanding that the buyers will test them in actual use and determine for themselves their adaptability to their intended uses.